



Northstate

Simply better carpet.

GATEWOOD XL PRODUCT BULLETIN

ABN 14010558540

Fibre System	100% Nylon 30% pre-consumer recycled content in face fibre
Coloration	UniColor™ fibre colour system
Construction	Multi-Level Loop Pile
Pile Weight	30 oz/sq yd 1017 g/sq m
Backing System	FullCircle Backing: 10% post-consumer recycled content
Carpet Protection	Anti-microbial & BioFresh™ present in backing laminate. PermaSeal™ protection against soiling.
Fire Hazard Properties (B.C.A. Spec.C1.10a)	Direct-Stick - Tested to AS/ISO 9239-1 Suitable for <i>ALL</i> building classifications. Conventional & Double-Bond with underlay – Tested to AS/ISO 9239-1 Suitable for <i>ALL</i> building classifications, <u>except non-sprinklered</u> Class 9a (Patient Care) and Class 3 (Accommodation for the Aged) Verify building classifications with your local building authority and/or council. <i>Consult your Northstate representative for specific details.</i>
Static Generation	< 3.0kv
Light Fastness	L5
Change on Wet Cleaning	Gray Scale 5
Approx pattern repeat	Width 30cm x Length 46cm
Installation Method	Suitable for direct-stick
Chair Protectors	Mandatory under chairs with castors to preserve appearance retention, and avoid premature wear.
Rating 15 Year Commercial Limited Warranties <i>see full warranty text for details</i>	Commercial Extra Heavy Duty (including stairs) Abrasive Wear UniColor™ Stain, UniColor™ Side Match Anti-Shock No Delamination ColourFast

- Installation to be in accordance with **Northstate Carpet Mills Technical Bulletin - Installation Procedures and Requirements, and ASNZS 2455.1:2007**. In direct-stick installations, all seams and cross joins must be sealed with a seam sealing adhesive. In double-bond and carpet gripper installations, all edges to be seamed must be sealed first with an edge sealing adhesive and an appropriate hot-melt adhesive seaming tape must be applied to all seams and cross joins. All unprotected edges must be sealed with an edge sealing adhesive.
- Pattern carpet with directional designs may be subject to pattern distortion. Exact colour & / or texture pattern match cannot be guaranteed.
- Carpets with linear designs and in particular, carpets constructed with contrasting colours side by side to produce a sisal effect may be subject to random colour banding across the carpet. Due to dyelot variations, actual material may vary from sample.
- Full details and explanations can be found on our website www.northstatecarpets.com.au

NORTHSTATE CARPET MILLS PTY LTD reserves the right to modify this specification to improve the product without prior notice and without prejudice.

E & O E



Rating

Commercial Extra Heavy Duty (including stairs)
15 Year Commercial Limited Warranties
Abrasive Wear UniColor™ Stain, UniColor™ Side Match
Anti-Shock No Delamination ColourFast

see full warranty text for details



Fire Hazard Properties (B.C.A. Spec C1.10a)

Direct-Stick - Tested to AS/ISO 9239-1
Suitable for *ALL* building classifications.
Conventional & Double-Bond with u/lay – Tested to AS/ISO 9239-1
Suitable for *ALL* building classifications, except non-sprinklered
Class 9a (Patient Care) and Class 3 (Accommodation for the Aged)
Verify building classifications with your local building authority and/or council.
Consult your Northstate representative for specific details.



UniColor™ Stain

Our UniColor™ Stain Warranty covers all commercial environments for most food and beverage spills. Spots can be removed, or we'll replace the carpet including labour.

Some limitations apply: see full warranty text



UniColor™ Side Match

UniColor™ means uniform colour. UniColor™ eliminates installation matching concerns. Unlike conventional carpet dying, no roll sequencing is required: the left side of the first roll matches the right side of the last roll in the production lot.

Some limitations apply: see full warranty text



BioFresh™ Anti-microbial

This carpet incorporates BioFresh™ anti-microbial treatment to inhibit the growth of bacteria, fungi and mildew, ensuring lasting hygienic freshness.

Carpets with BioFresh™ are ideal for areas where spills and soil could promote bacterial growth.



Sustainability / Environmentally Friendly

This product contains 30% pre-consumer recycled content in face fibre, and 10% post-consumer recycled content in backing.